

UELZENER

MASCHINEN GMBH



ESTROMAT 404

Continuous Mixer for dry mortar
Different types for 230V single phase
or 400V three phase available



UELZENER MASCHINEN GMBH

Stahlstrasse 26-28

D-65428 Rüsselsheim / Germany

T: +49-6142-17768-0 F: +49-6142-17768-50

Homepage: www.uelzener-ums.de e-mail: contact@uelzener-ums.de

UELZENER



The ESTROMAT 404 continuous mixer can be moved at the site like a wheelbarrow.



The water dosage armature is mounted at a comfortable working level and assures an exactly continuous mortar consistency



The cleaning of the ESTROMAT 404 is very easy. Clean mixing shaft and mixing pipe with water - finished!



The functional machine combination ESTROMAT 404, mortar pump PUTZ-KNECHT S 30 and compressor allow easy mixing, pumping and spraying also of difficult mortar types.



The mixing time can be optimally adapted to the mortar by using different mixing pipe length and shafts. The extension is increasing the hopper volume by about 100 litres.



With only a few hand movements the ESTROMAT 404 is dismantled in four parts: mixing pipe, mixing shaft, frame and hopper. The unit can be easily transported in a car.

Description

The ESTROMAT 404 is a continuous mixer for the mixing of dry ready mixed mortar. Turn the starter button and the mortar is delivered ready to use on trowels in a constant consistency and in each required quantity.

Whatever the material is, whether cement mortar, insulation or wall plaster, scraper render, floor screed or fine concrete, the ESTROMAT 404 will mix it all optimally. For the different materials 2 different types of dosage shafts are available.

The unit is quickly ready to start and easy to handle, which makes the

ESTROMAT 404 the ideal continuous mixer for smaller construction sites and renovation works, which have been carried out by hand mixers until now.

The ESTROMAT 404 has a robust 2,2kW gear motor for 230V or 3 kW 400V/50Hz.

The handling of the ESTROMAT 404 is extremely easy:

- Plug in Shock-proof plug
- Connect water hose
- Fill in dry ready mixed mortar
- Adjust mortar consistency

and immediately you will receive up

to 25l/min continuously mixed mortar.

The frame of the ESTROMAT 404 is equipped with 2 hard rubber rolls, so that the mixer can be easily moved. By the water dosage armature the mortar consistency can be adjusted exactly to the requirements.

As only the mixing (wet) zone has to be cleaned – pull mixing pipe off and take mixing shaft out, clean both with water – the cleaning time is considerably short.

The outlet height of the mixing pipe allows that a wheelbarrow can be placed below.

Technical Data

Mixing output	:	appr. 25 l/min
Drive 230V/50Hz/ 1Ph	:	2,2kW
Drive 400V/50Hz/ 3Ph	:	3kW
Fuses	:	16 Amp/slow
Water pressure	:	min 2 bars

Size / weight

Length	:	1850 mm
Width	:	600 mm
Height	:	970 mm
Weight	:	100 kg

Scope of Delivery

Material hopper with bag cutter
 Mixing and dosage shaft
 Machine frame with 2 rolls
 Compact-water dosage armatures
 flow meter on request

